

KEN WASHER DISINFECTOR IQ5

# Intelligent Quality

- The Future of Efficient Disinfection

- ✓ Easy to use
- ✓ Easy to service
- ✓ Easy to choose

The IQ series is a modular built range that meets all relevant standards such as ISO 15883, UL to name a few.

The elegant design provides a smooth surface in tempered glass that is easy to clean. The IQ5 has downward sliding doors that allows for manual loading, or the use of a unique automatic loading that provides high flexibility and uses very little space.

The IQ5 is easy to operate by touch panel with swipe function, showing all relevant information of the program needed by the operators.

IQ5 has the lowest energy and water consumption in the market, to keep operating costs at a minimum and contribute to a clean environment.

IQ5 comes with a wide range of racks and modules and holds up to 12 DIN baskets.

All data from the IQ5 are fully exchangeable with common computer systems.



# HEALTHCARE



The IQ series is available with a lot racks, modules and distributors. Contact your dealer or look at our web page for equipment and catalogues.

## Advantages:

### Environment

- Low energy costs
- Low noise level
- Low chemical usage
- Very low water consumption

### Technology

- RFID recognition
- Intuitive smart display PCTP as option
- Drop down door serves as loading platform
- Service access from the front

### Hygiene safety

- EN 62366 tested
- EN ISO 15883-1-2-5
- Glass surfaces easy to clean

### Validation of all processes

- Open programs structure
- Full process validation
- Exchange of data
- Printer

Description	Values
<b>Outer dimensions</b>	H: 1985 x W: 662 x D: 711 mm
<b>Operative chamber dimensions</b>	H: 690 x W: 550 x D: 625 mm
<b>Weight excl./incl. packaging</b>	236 / 316 kg
<b>Operative volume, wash chamber</b>	239 L
<b>Total volume, wash chamber</b>	256 L
<b>Capacity DIN-baskets 480x250x50</b>	12
<b>Cycle time, standard</b>	35-45 min (fast cycle machine <30 min)
<b>Exhaust connections</b>	ø100 mm 250 m3 per hour
<b>Water connections</b>	2 x 3/4 (3rd is optional)
<b>Cold water</b>	200-800 kPa, ≥ 15 L/min, 5-30°C, 0-30° dH
<b>Hot water</b>	200-800 kPa, ≥ 15 L/min, 30-70°C, 0-3° dH
<b>Deminerlized / RO water</b>	200-800 kPa, ≥ 15 L/min, 5-70°C - option
<b>Washing / Drying</b>	<53 dB (A) / <55 dB (A)
<b>Water consumption per phase</b>	Approx. 12-15 L (standard 5-level rack)
<b>Power supply options</b>	3x200-480V AC + N + PE, 50/60 Hz 7-13 kW
<b>Programs available</b>	10 standard + 30 optional
<b>Drain</b>	ø50 mm

Contact a KEN partner

Clean, Lean & Green